

# DNX model tip numbers



Model No.	Minimum Orifice Diam (mm)	Flow rate lpm @ bar					Spray angle @ 150 bar
		10	100	150	200	250	
0525	1.9	9.5	30	36.8	42.4	47.4	27
0532	1.8	9.5	30	36.8	42.4	47.4	35
0540	1.7	9.5	30	36.8	42.4	47.4	43
0625	2.1	11.4	36.0	44.1	50.9	56.9	27
0632	2.0	11.4	36.0	44.1	50.9	56.9	35
0640	1.9	11.4	36.0	44.1	50.9	56.9	43
0725	2.3	13.3	42.0	51.4	59.4	66.4	27
0732	2.2	13.3	42.0	51.4	59.4	66.4	35
0740	2.1	13.3	42.0	51.4	59.4	66.4	43
0825	2.5	14.3	45.3	55.5	64.1	71.6	27
0832	2.3	14.3	45.3	55.5	64.1	71.6	35
0840	2.2	14.3	45.3	55.5	64.1	71.6	43
0925	2.6	17.1	54.0	66.1	76.4	85.4	27
0932	2.5	17.1	54.0	66.1	76.4	85.4	35
0940	2.4	17.1	54.0	66.1	76.4	85.4	43
1125	3.1	21.4	67.7	82.9	95.7	107	27
1132	2.8	21.4	67.7	82.9	95.7	107	35
1140	2.7	21.4	67.7	82.9	95.7	107	43
1325	3.2	24.5	77.5	94.9	110	123	27
1332	3.1	24.5	77.5	94.9	110	123	35
1340	2.9	24.5	77.5	94.9	110	123	43
1525	3.5	28.6	90.5	111	128	143	27
1532	3.3	28.6	90.5	111	128	143	35
1540	3.2	28.6	90.5	111	128	143	43

Other tips available upon request