

# MMA Mini Atomise Nozzle




The MMA produces fine droplets in a wide full cone spray pattern. It is available as either a pressure spray or siphon spray set-up. It can use the lowest available flow and is highly clog resistant. It is used for the cleaning of gate roll, backing roll and size roll, canvas chemical washing of parts, humidity regulation, and moisturising.




## Construction

Constructed of SS303.



Model number	Minimum orifice diameter for liquid (mm)	Air flow rate (ℓ/min(Nor.)) (air pressure : 0.3MPa)	Water flow rate (mℓ/min)	Connecting threads		Weight (g)	Dimensions (mm)		
				Liquid	Air		D	H	L
50W	1.5	50	5~100	Rc 1/8	Rc 1/8	60	21	19	33
100W	2.0	100	10~200	Rc 1/8	Rc 1/4	80	23	21	38
200W	2.0	200	25~500	Rc 1/8	Rc 1/4	80	23	21	38
500W	2.5	500	50~1000	Rc 1/4	Rc 1/2	280	35	32	58
1000W	3.0	1000	100~2000	Rc 1/4	Rc 1/2	280	35	32	58



Model number	Spray width (mm)			
	W 1	W 2	W 3	
MMA	50W	25~30	50~55	110~130
	100W	30~35	55~60	130~150
	200W			
	500W	40~45	70~80	180~200
	1000W			

Spray angle is approx. 30° at 0.3 MPa, will be wider at lower pressure.