


## C9

Manufactured in 303ss (316ss available) with 9/16" or 1/4" thread.

Flow rates from 0.75 lpm to 9.42 lpm depending upon pressure.

To be used in conjunction with existing shower headers, or with ICS shower headers.

Ideal where contaminated water is used. I.e. white water in the pulp and paper industry.



Model	Connection	Orifice mm	Lpm @ bar		
			3	10	20
1 C9 08	1/4" BSP	0.8	0.75	1.37	1.94
1 C9 08C	1/4" BSPT	0.8	0.75	1.37	1.94
1 C9 1	1/4" BSP	1.00	0.95	1.73	2.45
1 C9 1	1/4" BSPT	1.00	0.95	1.73	2.45
1 C9 1.6C	1/4" BSPT	1.6	2.30	4.20	5.94
1 C9 2	1/4" BSP	2.00	3.65	6.66	9.42
1 C9 2C	1/4" BSPT	2.00	3.65	6.66	9.42
C9 07	9/16"	0.77	0.56	1.02	1.44
C9 08	9/16"	0.8	0.75	1.37	1.94
C9 1	9/16"	1.00	0.95	1.73	2.45
C9 1.2	9/16"	1.2	1.27	2.31	2.58
C9 2	9/16"	2.00	3.65	6.66	9.42

