

# DBL Full Cone

Precision, low flow nozzle with uniform distribution in a solid spray pattern.

Uniform distribution of finely atomised droplets

Available with 1/8"BSPT thread

Standard spray angles - 45°, 60°, 90°

Other spray angle available

Strainer is optional - see chart for mesh size

Materials

Brass

Stainless steel

Other materials to order



Shown with optional filter

Model DBL	Thread size	Flow lpm @ bar						
		0.7	1	2	3	4	6	7
	1/8							
3	x	0.12	0.14	0.19	0.24	0.27	0.34	0.36
4	x	0.15	0.18	0.26	0.32	0.37	0.45	0.48
5	x	0.19	0.23	0.32	0.40	0.46	0.56	0.60
6	x	0.23	0.27	0.39	0.47	0.55	0.67	0.72
7	x	0.27	0.32	0.45	0.55	0.64	0.78	0.85
8	x	0.31	0.37	0.52	0.63	0.73	0.89	0.97
9	x	0.34	0.41	0.58	0.71	0.82	1.00	1.09
10	x	0.38	0.46	0.65	0.79	0.91	1.12	1.21
12	x	0.46	0.55	0.77	0.95	1.10	1.34	1.45
14	x	0.54	0.64	0.90	1.11	1.28	1.57	1.68
16	x	0.61	0.73	1.03	1.27	1.46	1.78	1.93
18	x	0.69	0.82	1.16	1.42	1.64	2.02	2.17
20	x	0.76	0.91	1.29	1.58	1.82	2.23	2.42
25	x	0.96	1.14	1.61	1.98	2.28	2.80	3.02
30	x	1.14	1.37	1.93	2.37	2.73	3.35	3.62

